
Resin type

Spacer of round shape for printed board [BP, 4BP series] (100pcs/pack)


- This is used for fitting a printed board to a chassis, and other adaptive cases.
- Material: Acetal copolymer(UL94HB)
- Color: Black
- Operating temperature range: −40 to + 85 °C



For M3 screw

Part number	A(mm)	L(mm)
BP-5	Through hole	5
BP-7.5	Through hole	7.5
BP-10	Through hole	10
BP-12.5	Through hole	12.5
BP-15	6	15
BP-17.5	6	17.5
BP-20	6	20
BP-25	6	25
BP-30	6	30





For M4 screw

Part number	L(mm)
4BP-4	4
4BP-5	5
4BP-6	6
4BP-7	7
4BP-8	8
4BP-9	9
4BP-10	10
4BP-11	11
4BP-12	12
4BP-13	13
4BP-14	14
4BP-15	15
4BP-16	16
4BP-17	17
4BP-18	18
4BP-19	19
4BP-20	20
4BP-25	25
4BP-30	30

Spacer of hexagon shape for printed board [CQ series] (100pcs/pack)

- The whole part of this spacer is resin.
- Material: Special polyamide resin (UL94HB)
- Color: Black
- ullet Operating temperature range: -40 to + 125 $^{\circ}$ C
- Tightening torque: 2.5kg.f.cm or less

Part number

Part number	П
CQ-8	8
CQ-10	10
CQ-15	15
CQ-20	20



