PEEK® spacer of hexagon shape [3MPP, 4MPP series] (20pcs/pack)

- This material has excellent heat resistance and chemical resistance properties.
- Material: PEEK® (UL94V-0)
- Color: Brown
- Operating temperature range: -40 to +200°C


■ 3MPP type (for M3)


- OWN I type	- (101 1110)	
Part number	A(mm)	L(mm)
3MPP- 4	Through hole	4
3MPP- 5	"	5
3MPP- 6	11	6
3MPP- 7	11	7
3MPP- 8	"	8
3MPP- 9	11	9
3MPP-10	//	10
3MPP-11	11	11
3MPP-12	"	12
3MPP-13	"	13
3MPP-14	//	14
3MPP-15	6	15
3MPP-16	6	16
3MPP-17	6	17
3MPP-18	6	18
3MPP-19	6	19
3MPP-20	6	20
3MPP-25	6	25
3MPP-30	6	30

■ 4MPP type (for M4)

- ivii i typo (ioi ivi i)			
A(mm)	L(mm)		
Through hole	4		
11	5		
11	6		
//	7		
//	8		
11	9		
//	10		
//	11		
//	12		
11	13		
11	14		
11	15		
//	16		
11	17		
8	18		
8	19		
8	20		
8	25		
8	30		
	Through hole // // // // // // // // // // // // /		









PEEK® screw, nut [MPE series] (20pcs/pack)

- This screw has excellent heat resistance and chemical resistance properties.
- Material:PEEK® (UL94V-0)
- Color: Brown
- Operating temperature range: −40 to +200°C






Part number	L(mm)
2MPE- 4	4
2MPE- 5	5
2MPE- 6	6
2MPE- 8	8
2MPE-10	10




Part number	L(mm)	
2.6MPE- 6	6	
2.6MPE- 8	8	
2.6MPE-10	10	
2.6MPE-12	12	

M3 P=0.5
5.5%
ry .
2 L

Part number	L(mm)	
3MPE- 6	6	
3MPE- 8	8	
3MPE-10	10	
3MPE-12	12	
3MPE-16	16	
3MPE-20	20	



Part number	L(mm)	
4MPE- 6	6	
4MPE- 8	8	
4MPE-10	10	
4MPE-12	12	
4MPE-16	16	
4MPE-20	20	
4MPE-25	25	



Part number	Α	В	С
3MPE-N	5.5	2.4	МЗ
4MPE-N	7	3.2	M4

^{*} PEEK is the registered trade mark of Victrex-MC, Inc.